



OMNIPOWER

THE POWER OF CHOICE

48V LiFeYPO4 Battery (Lithium Iron Yttrium Phosphate)

- Includes Battery Management system, cell monitoring and voltage control
- Built-in fuse and DC isolator
- Integrated with leading solar inverters to ensure optimal battery charging for prolonged battery life.

HIGH ENERGY, HIGH PERFORMANCE ENERGY STORAGE SOLUTIONS.



Shelf Price < Lead Acid shelf price

Daily cycle for more than 10 years

Weight < 25 % of Lead Acid

Volume < 33% of Lead Acid

100% Environmentally friendly

100% Safe

Lithium Iron Phosphate (LiFeYPO4) batteries have transfer efficiencies of more than 96% at C/2 charge and discharge rates they deliver 10 times higher turn around efficiencies than leading lead acid batteries. This feature implies major savings in the necessary size of the solar system required to charge the batteries.

LiFeYPO4 batteries are capable of delivering up to 80% of their charge for more than 5000 times and are perfectly suited for operation in warm African conditions.

LiFeYPO4 batteries have more than 4 times the energy density compared to Lead Acid equivalents. This has great advantages for application where light weight energy storage is a requirement. Applications such as 4x4 vehicles, yachts and even apartment buildings benefit greatly from these light weight batteries. No gassing, no ventilation required.

Available from **12V, 24V, 36V, 48V** up to **800V** with storage capacities from 1.8 kWh for small residential applications to 1080kWh for industrial applications.



OMNIPOWER

THE POWER OF CHOICE

LiFeYPO4 Lithium Iron Yttrium Phosphate Battery

| MODEL | OPR48V-77-4k | OPR48V-115-6k | OPR48V-154-8k | OPR48-230-12k |
|--|---|-----------------|-----------------------|-----------------------|
| GENERAL | | | | |
| Battery Type | LiFeYPO4 (Lithium Iron Yttrium Phosphate) | | | |
| Useable Capacity | 4 000 Wh | 6 000 Wh | 8 000 Wh | 12 000 Wh |
| Nominal Voltage | 48 VDC | | | |
| Operating Voltage | 46.4 VDC - 56.2VDC | | | |
| Operating Temperatures | -20°C to 65°C | | | |
| Cycle Life > 3600 Cycles (100% DoD) | 4 000 Wh | 6 000 Wh | 8 000 Wh | 12 000 Wh |
| Cycle Life > 5000 Cycles (80% DoD) | 3 200 Wh | 4 800 Wh | 6 400 Wh | 9 600 Wh |
| Cycle Life > 7000 Cycles (70% DoD) | 2 800 Wh | 4 200 Wh | 5 600 Wh | 8 400 Wh |
| Dimensions L x W x H (mm) | 710 x 230 x 265 | 660 x 360 x 280 | 2 x (710 x 230 x 265) | 2 x (660 x 360 x 280) |
| Net Weight (kg) | 47 kg | 75 kg | 2 x 47 kg | 2 x 75 kg |
| Warranty | 10 Years | | | |
| CHARGE | | | | |
| Bulk Voltage | 56.2 VDC | | | |
| Discharge Voltage (min) | 46.4 V | | | |
| Max. Charge Current (cont.) | 160 A | 200 A | 300 A | 400 A |
| Max. Discharge Current (cont.) | 160 A | 200 A | 300 A | 400 A |
| Max. Discharge Current (burst @ 1 min) | 200 A | 300 A | 400 A | 600 A |
| Max. Discharge Current (peak @ 10 sec) | 550 A | 550 A | 1200 A | 1200 A |
| Self-discharge Rate | < 2% per month | | | |
| Charge / Discharge Efficiency | 96% @ C2; 98% @C10 | | | |
| PROTECTION | | | | |
| Isolator | 200 A | 300 A | 400 A | 600 A |
| In-line Fuse | 200 A | 300 A | 400 A | 600 A |
| Over Current Protection | 200 A | 300 A | 400 A | 600 A |
| Over Voltage Cut-out | 64.0 V (4.0 V on any cell) | | | |
| Under Voltage Cut-out | 45.6 V (2.85 V on any cell) | | | |

| MODEL | OPR48V-310-16k | OPR48V-460-24k | OPR48V-770-40k | OPR48-1250-65k |
|--|---|-----------------------|------------------|-------------------|
| GENERAL | | | | |
| Battery Type | LiFeYPO4 (Lithium Iron Yttrium Phosphate) | | | |
| Useable Capacity | 16 000 Wh | 24 000 Wh | 40 000 Wh | 65 000 Wh |
| Nominal Voltage | 48 VDC | | | |
| Operating Voltage | 46.4 VDC - 56.2VDC | | | |
| Operating Temperatures | -20°C to 65°C | | | |
| Cycle Life > 3600 Cycles (100% DoD) | 16 000 Wh | 24 000 Wh | 40 000 Wh | 65 000 Wh |
| Cycle Life > 5000 Cycles (80% DoD) | 12 800 Wh | 19 200 Wh | 32 000 Wh | 52 000 Wh |
| Cycle Life > 7000 Cycles (70% DoD) | 11 200 Wh | 16 800 Wh | 28 000 Wh | 45 500 Wh |
| Dimensions L x W x H (mm) | 4 x (710 x 230 x 265) | 4 x (660 x 360 x 280) | 735 x 785 x 1130 | 1300 x 650 x 1200 |
| Net Weight (kg) | 4 x 52 kg | 4 x 75 kg | 450 kg | 820 kg |
| Warranty | 10 Years | | | |
| CHARGE | | | | |
| Bulk Voltage | 56.2 VDC | | | |
| Discharge Voltage (min) | 46.4 V | | | |
| Max. Charge Current (cont.) | 400 A | | | |
| Max. Discharge Current (cont.) | 400 A | | | |
| Max. Discharge Current (burst @ 1 min) | 600 A | | | |
| Max. Discharge Current (peak @ 10 sec) | 1 200 A | | | |
| Self-discharge Rate | < 2% per month | | | |
| Charge / Discharge Efficiency | 96% @ C2; 98% @C10 | | | |
| PROTECTION | | | | |
| Isolator | 600 A | | | |
| In-line Fuse | 600 A | | | |
| Over Current Protection | 600 A | | | |
| Over Voltage Cut-out | 64.0 V (4.0 V on any cell) | | | |
| Under Voltage Cut-out | 45.6 V (2.85 V on any cell) | | | |

