



K A C O 
new energy.

Data sheet

Powador

2002 | 3002 | 4202

5002 | 6002

High flexibility. Easy installation.

The galvanically isolated string inverters Powador 2002–6002.

The inverters from the Powador 2002 to Powador 6002, with galvanic isolation, feature effortless installation, the highest degrees of efficiency, and optimum operation with thin-film modules – and make designing a PV system a piece of cake.

Installation is problem-free: All required connections for communication – RS485, S0 and fault signalling relay – are located on a single circuit board in the housing and can be connected easily. The DC switch is integrated into the units as a matter of course. They achieve an outstanding efficiency of up to 96 %.

Using a Powador 02 inverter, you can build your next PV installation wherever you want: The software knows the in-

ternational requirements. This helps you to quickly and easily connect your PV installation to the grid – simply select the appropriate country setting and display language during installation.

The Powador 02 series skillfully makes use of the advantages of galvanically isolated inverters. The wide input voltage range allows you to be extremely flexible in planning your PV installation. Where transformerless units are out of the question, the Powador 02 series can handle even complex PV system designs.

In addition, KACO new energy offers a generator earthing kit for this series. Thin-film modules often require gene-

rator earthing for a long service life. Moreover, the inverters can display the earthing status of the PV generator – important information especially for the safe operation of thin-film modules.

From third quarter on, these units will be able to feed in reactive power.

Technical data

Powador 2002 | 3002 | 4202 | 5002 | 6002

| Electrical data | 2002 | 3002 |
|--------------------------------|---|---|
| Input variables | | |
| PV max. generator power | 2 000 W | 3 000 W |
| MPP range | 125 V ... 510 V | 200 V ... 510 V |
| No-load voltage | 600 V* | 600 V* |
| Max. input current | 14.3 A | 13.5 A |
| Number of strings | 3 | 3 |
| Number of MPP trackers | 1 | 1 |
| Inverse polarity protection | short-circuit diode | short-circuit diode |
| Output variables | | |
| Rated output | 1 650 W | 2 500 W |
| Max. output | 1 650 W | 2 500 W |
| Supply voltage | acc. to local requirements | acc. to local requirements |
| Rated current | 7.2 A | 10.9 A |
| Rated frequency | 50 Hz / 60 Hz | 50 Hz / 60 Hz |
| cos phi | 0.80 inductive ... 0.80 capacitive** | 0.80 inductive ... 0.80 capacitive** |
| Number of grid phases | 1 | 1 |
| General electrical data | | |
| Max. efficiency | 95.9 % | 96.0 % |
| European efficiency | 95.3% | 95.4 % |
| Night consumption | 0.4 W | 0.4 W |
| Switching plan | self-commutated, galvanically isolated, HF transformer | self-commutated, galvanically isolated, HF transformer |
| Network monitoring | acc. to local requirements | acc. to local requirements |
| Mechanical data | | |
| Display | LCD 2 x 16 characters, LED | LCD 2 x 16 characters, LED |
| Control units | 2 buttons for display control | 2 buttons for display control |
| Interfaces | RS485, S0 | RS485, S0 |
| Fault signalling relay | potential-free NOC max. DC 30 V / 3 A max. AC 250 V/1.5A | potential-free NOC max. DC 30 V / 3 A max. AC 250 V/1.5A |
| Connections | PCB terminals inside the unit (max. cross section. 6 mm ² flexible), Cable connection via cable fittings (DC fitting M16, AC fitting M32) | |
| Ambient temperature | -20 °C ... +60 °C*** | -20 °C ... +60 °C*** |
| Cooling | free convection / no fan | free convection / no fan |
| Protection class | IP54 | IP54 |
| Noise emission | < 35 dB (A) (noiseless) | < 35 dB (A) (noiseless) |
| DC switch | integrated | integrated |
| Casing | aluminium | aluminium |
| H x W x D | 450 x 340 x 200 mm | 500 x 340 x 200 mm |
| Weight | 14.5 kg | 20 kg |

Applicable standards and regulations are taken into account for each country version that is set.

* To protect the hardware, the inverter starts up only at voltages < 550 V / **with the passing of the German Low Voltage irective in Q3/2011
***Power derating at high ambient temperatures

| 4202 | 5002 | 6002 |
|---|---|---|
| Input variables | | |
| 4 200 W | 5 000 W | 6 000 W |
| 200 V ... 510 V | 200 V ... 510 V | 200 V ... 510 V |
| 600 V* | 600 V* | 600 V* |
| 18.5 A | 22.4 A | 26.5 A |
| 3 | 3 | 3 |
| 1 | 1 | 1 |
| short-circuit diode | short-circuit diode | short-circuit diode |
| Output variables | | |
| 3 500 W | 4 200 W | 5 000 W |
| 3 500 W | 4 200 W | 5 000 W |
| acc. to local requirements | acc. to local requirements | acc. to local requirements |
| 15.2 A | 18.3 A | 21.7 A |
| 50 Hz / 60 Hz | 50 Hz / 60 Hz | 50 Hz / 60 Hz |
| 0.80 inductive ... 0.80 capacitive** | 0.80 inductive ... 0.80 capacitive** | 0.80 inductive ... 0.80 capacitive** |
| 1 | 1 | 1 |
| General electrical data | | |
| 95.9 % | 95.9 % | 95.9 % |
| 95.1 % | 95.3 % | 95.3 % |
| 0.4 W | 0.4 W | 0.4 W |
| self-commutated, galvanically isolated, HF transformer | self-commutated, galvanically isolated, HF transformer | self-commutated, galvanically isolated, HF transformer |
| acc. to local requirements | acc. to local requirements | acc. to local requirements |
| Mechanical data | | |
| LCD 2 x 16 characters, LED | LCD 2 x 16 characters, LED | LCD 2 x 16 characters, LED |
| 2 buttons for display control | 2 buttons for display control | 2 buttons for display control |
| RS485, S0 | RS485, S0 | RS485, S0 |
| potential-free NOC max. DC 30 V / 3 A max. AC 250 V/1.5A | potential-free NOC max. DC 30 V / 3 A max. AC 250 V/1.5A | potential-free NOC max. DC 30 V / 3 A max. AC 250 V/1,5A |
| PCB terminals inside the unit (max. cross section. 6 mm ² flexible, 10 mm ² rigid), Cable connection via cable fittings (DC fitting M16, AC fitting M32) | | |
| -25 °C ... +60 °C*** | -25 °C ... +60 °C*** | -25 °C ... +60 °C*** |
| free convection / no fan | fan | fan |
| IP54 | IP54 | IP54 |
| < 35 dB (A) (noiseless) | < 45 dB (A) (fan) | < 45 dB (A) (fan) |
| integrated | integrated | integrated |
| aluminium | aluminium | aluminium |
| 600 x 340 x 240 mm | 600 x 340 x 240 mm | 600 x 340 x 240 mm |
| 26 kg | 28 kg | 28 kg |


Applicable standards and regulations are taken into account for each country version that is set.

* To protect the hardware, the inverter starts up only at voltages < 550 V / **with the passing of the German Low Voltage irective in Q3/2011
***Power derating at high ambient temperatures



Graphical display of efficiency

3D efficiency diagram for Powador 6002



Powador 2002 | 3002 4202 | 5002 | 6002

Degree of efficiency up to 96.0 %

Optimized MPP tracking for higher yield


Grounding of PV generator possible
Optimally suited for thin-film modules

5-years factory warranty plus 2-years when the unit is registered

Asymmetry monitoring via special KACO Sym-Bus in Q3/2011

Capable of reactive power

Efficiency characteristic curves for Powador 6002



Your retailer