PV SOLAR CONNECTORS & SOLAR CABLE

X-MC4 TYPE :

Tuv certificate (EN 50521)
Design according to IEC6125-IEC61730
RoHS compliant
Material:PPO/PA
Temperature range:-40degC +90degC
Connector protection rating:IP67(Mated)
External cable diameter:5.5mm to 7.2mm

X-MC4T BRANCH TYPE :

Tuv certificate (EN 50521)
Design according to IEC6125-IEC61730
RoHS compliant
Material:PPO/PA
Temperature range:-40degC +90degC
Connector protection rating:IP67(Mated)

X-2T1 MC4T TYPE :

Tuv certificate (EN 50521)
Design according to IEC6125-IEC61730
RoHS compliant
Material:PPO/PA
Temperature range:-40degC +90degC
Connector protection rating:IP67(Mated)

X-3T1 MC4T TYPE :

Tuv certificate (EN 50521)
Design according to IEC6125-IEC61730
RoHS compliant
Material:PPO/PA
Temperature range:-40degC +90degC
Connector protection rating:IP67(Mated)

X-MC4Y BRANCH TYPE 4-WAY:

Tuv certificate (EN 50521)
Design according to IEC6125-IEC61730
RoHS compliant
Material:PPO/PA
Temperature range:-40degC +90degC
Connector protection rating:IP67(Mated)

SOLAR CABLE - 4 & 6mm^2:

4mm^2/ 6mm^2
Black and Red
Cut to required lengths
High quality solar cable

SINETECH
THE POWER OF CHOICE

2 Samantha Street, Strijdom Park,
Randburg, Johannesburg, 2194
Tel: (+27) 11 886-7874 | Fax: (+27) 11 787 0178
sales@sinetech.co.za | sinetechstore.co.za